



Linea 20 LED Light line

Mechanical properties	
Dimensions (WxH)	20x20 mm
Standard Length (mm)	600 – 900 – 1200 – 1500 – 1800 mm (other sizes on request)
Material housing	Aluminium
Finishing Housing	Coating 2 layers, BLACK RAL 9005
Electronics protection	Fully inducted, polyurethane resin, self extinguishing.
Degree of protection	IP67
Impact resistance	IK08
Confirmation	M4 Inserts
Clean	Suitable for high-pressure cleaning
Electrical properties	
Connection voltage	24 VDC
MayN	10 W/M
ConnectionCable	1 meter, 2x0, 75 mm ²
Light	
Light source Type	Led
Color	Green (other colours on request)
Number of LEDs	40 per metre
Environmental conditions	
Suitable for	Indoor and outdoor
Temperature	-15°C+ 45°C
Relative humidity	15% – 100%
Life	
Technical Life span	> 25 years
Lifespan Light Source	50,000 h Tc 25° C
Warranty	
Warranty	5 years Carry-in

Westend Lighting develops and produces in its factory in Roosendaal. Besides our standard Products we can also develop and produce tailormade products for you. Please contact us for more information.

Westend Lighting B.v.

Loam Street 44, 4705 RH Roosendaal, the Netherlands

Tel: + 31 (0) 85 487 9670

Email sales@westendlighting.eu

Member of NDF Group

Delivery Ex. Works | Changes reserved | REV 1En -2019-5-15